

LSM80

TECHNICAL DATA SHEET



PUMP APPLICATIONS:

- Sewage Treatment plants
- Combinet heat and power plants
- Fishing industry
- Meat plants
- Chemical industry
- Food industry
- Off-Shore
- Mining
- Agriculture
- Biogas

PUMP ADVANTAGES:

- Low energy Consumption
- High pressure
- Self priming
- Tolerates dry-run
- Passes large objects
- Low maintenance

LSM • PUMPER

Sigenevej 7 | DK-9760 Vraa
Tel. +45 98 98 19 00 | Fax +45 98 98 24 40
www.lsm.dk

DEALER:

LSM80

TECHNICAL DATA SHEET

TECHNICAL DATA:

- **Nominal flowrate:** 20 m³/h
- **Nominal pressure:** 5 bar (4 kW motor)
- **Max. Pressure:** 10 bar
- **Connection:** MALE 3" BSP or DN80 SS Flange PN10 (DIN EN 1092-1)
- **Weight:** 500 kg
- Planetary gearbox and motor is selected for the specific pressure and flowrate needed.
- Optional with Variable Frequency Drive.
- High vacuum possible, suction lifts up to 8m. (Above 4m lifting height, vacuum is applied to the pump housing to improve efficiency).
- Low friction rollers
- Hot-Dip Galvanized / Powder Coated / Stainless Steel

Q [m³/h] Pump Flowrate

